

GMI SPMTA Trans-Ad®

3.5 Mil Matte White Opaque Calendered Vinyl

For Eco-Solvent, Solvent and UV-Solvent Based Inkjet Printers.



CONSTRUCTION

Applications	THIS PRODUCT IS INTENDED FOR use in high quality exterior marking or decals for temporary fleet graphic applications on smooth surfaces. Applications would include bus signs, automobiles and transportation signs.
Face Film	3.5 + 0.2 mils. Matte white opaque polymeric flexible vinyl
Adhesive Release	Clear acrylic pressure activated removable
Liner	90# (6.5 + 0.2 mils) white polyethylene coated two side-silicone coated one side paper

PHYSICAL PROPERTIES

Outdoor Durability	Three to five years mid-continental USA vertical exposure
Print Methods	Solvent, Eco-Solvent or UV curable screen printing inks.
Minimum Surface/Ambient Air Application Temperature	+40° F
Service Temperature Range	-20° F to + 150° F
Opacity	Excellent.
Typical Film Caliper (w/Adhesive)	11.0 – 12.0 mils
Chemical Resistance	Good for most petroleum based solvents. Edge sealing is recommended in high solvent exposure areas.
Water Resistance	Good.
Adhesion	25 + 2 oz./in.
Finish	Matte.
Shelf Life	One year when stored under conditions of 70 F and 50% relative humidity.

Sizes	SPMTA3050N	30" X 50 YDS
	SPMTA5450N	54" X 50 YDS
	SPMTA6050N	60" X 50 YDS

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2008 Graphic Materials International.
All rights reserved. SPMTA 050508