



GMI SPMVW Vehicle Wrap
2 Mil White Cast Vinyl

For Eco-Solvent and Solvent-Based Inkjet Printers

With a gray block-out positionable adhesive removable within 2 years.
For simple curves, no corrugation or rivets.

CONSTRUCTION

Face Film	.002
Adhesive	Positionable solvent acrylic with a gray block-out primer
Release Liner	90# Polyethylene two sides layflat liner

PHYSICAL PROPERTIES

Outdoor Durability	7 years vertical exposure in a temperate climate	
Print Methods	Solvent, eco-solvent, thermal and UV inks.	
Minimum Surface/Ambient Air Application Temperature	+50° F for flat & curved surfaces	
Adhesion	Stainless steel substrate 180° peel @ 10 in./min. 73° F	
Emission Color	Gloss.	
Shelf Life	One year when stored at 70° F and 50% relative humidity.	
Sizes	SPMVW3025N	30" X 25 YDS
	SPMVW3050N	30" X 50 YDS
	SPMVW4825N	48" X 25 YDS
	SPMVW4850N	48" X 50 YDS
	SPMVW5425N	54" X 25 YDS
	SPMVW5450N	54" X 50 YDS
	SPMVW6025N	60" X 25 YDS
	SPMVW6050N	60" X 50 YDS

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.