

A Professional Finish Without A Lot Of Fuss

Compact and easy to use, the SEAL 44 Ultra is an ideal first laminator for businesses introducing image finishing. It's also a good complementary machine for those wanting to add to existing laminating services. It can handle a broad range of applications and materials up to 42 inches (1,065mm) wide, allowing you to quickly and professionally finish rigid and flexible indoor displays and floor graphics, as well as backlit and pop-up displays.

High-Quality Performance From A Full-Featured Laminator

The professional features of the SEAL 44 Ultra assure easy operation and high-quality output for every project. You can control the temperature settings and film tensions for use with a range of films and adhesives, for an even, smooth finish. Auto-grip shafts make quick work of loading your materials and the silicone-coated rollers make the whole process simple and easy to clean up afterwards.

All This And A Name You Can Trust

To assure the highest level of results for your projects, we recommend you use the SEAL 44 Ultra with the extensive range of laminating films and adhesives from SEAL Brands. And for the ultimate in simplicity, try ProSeal[™] pouch boards and pouches.



Features

- Touch pad control panel for easy use, with lighted indicators to show progress
- Single control knob to adjust for thicknesses up to 3/8" (10mm)
- Adjustable speed dial lets you control settings
- Auto-grip shafts for easy loading of materials
- Silicone-coated rollers for easy cleaning
- Three temperature settings for use with a wide range of films and adhesives: 125°F (50°C); 195°F (90°C); 250°F (120°C)
- Internal heating element assures even temperature across the length of the rollers
- Material shaft brake lets you adjust film tension for a flat and even finish
- Foot control for hands-free operation
- Comprehensive safety system with emergency stops



1. Single control knob to adjust for substrate thicknesses.
2. Simple control panel showing temperature and speed adjustments.



Auto-grip shafts for easy loading and positioning of materials plus integral brake for simple film tension adjustment.



Innovative method for removing release liners.

SEAL® 44 Ultra Laminator

SPECIFICATIONS

Specifications	SEAL 44 Ultra
Max. Working Width	44" (1117 mm)
Max. Speed	4.8 ft/min. (1.5 m/min.)
Max. Substrate Thickness	3/8" (10 mm)
Max. Roller temperature	250°F (120°C)
Dimensions	Width: 58" (1480 mm) Depth: 22" (570 mm) Height: 43" (1105 mm)
Net Weight	242 lbs. (110 kg)
Shipping Dimensions	Width: 67" (1700 mm) Depth: 27" (700 mm) Height: 27" (700 mm)
Shipping Weight	331 lbs. (150 kg)
Electrical Requirements	Single Phase 230 VAC, 50/60 Hz, 9A 110 VAC, 50/60 Hz, 16A
Safety Certification	cETL, CE

Seal Graphics Americas Corporation
7091 Troy Hill Drive
Elkridge, MD 21075
Tel: 410-379-5400
Fax: 410-579-8960

Seal Graphics Canada
1601 Matheson Blvd. E.
Mississauga, Ontario
Canada, L4W 1H9
Tel: 905-212-9232
Fax: 905-212-9313

Seal Graphics U.K. Ltd
Unit 1, 1 Watkins Close
Burnt Mills Industrial Estate
Basildon, Essex SS13 1BJ
United Kingdom
Tel: +44 1268 530 331
Fax: +44 1268 729 442

Seal Graphics Europe BV
Kanaaldijk O.Z.3
P.O.Box 29,
8100 AA Raalte
The Netherlands
Tel: +31 572 345 500
Fax: +31 572 345 501

Seal Graphics Pacific Limited
Unit A, 13th Floor, Block 1
Leader Industrial Centre
Tsuen Wan,
New Territories, Hong Kong
Tel: +852 2407 3738
Fax: +852 2408 0973



Contact your local distributor:

