

SolvoPrint™ Nolite 360

Product Specifications



Material Details		
Carrier Material	Polyester compound	
Thickness	350 µm	13.8 mil
Weight	420 g/m ²	12.39 oz/yd ²
Finish	Matte coating	
Storage Conditions	Store boxed at 10 – 25°C (50 – 77°F)	
Shelf Life	12 months	
Processing Conditions	18 - 25°C / 64 – 77°F at 40 - 65% relative humidity	

Areas of Application

- Pop Up and Rigid display systems
- Trade show and exhibit graphics
- Suitable for indoor and for short term outdoor application use

Advantages / Special Features

- High opacity film with silver light blocking backer
- Matte finish to eliminate glare under fluorescent/interior lighting
- Scratch resistant inkjet coating
- Excellent print quality
- Fast drying
- Part of Neschen's INDISPLAY Solutions

Printability	
Solvent	◆
Eco Solvent	◆
UV-curable	◆
Latex	Testing in progress

Process & Handling

- To avoid fingerprints, usage of cotton gloves is recommended
- For protective purpose usage of Neschen Protective Laminates is recommended (ensure adequate drying before lamination). 12 hours drying time is recommended.
- Store unused media in the original packaging

Recommended Protection Film

- SEAL® Print Shield Deep Crystal



Temperatures and thicknesses are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. Neschen has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the Neschen directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards. The purchaser should test material to determine if it is suitable for their own specific purpose.