

Material Details		
Carrier Material	Polyester compound	
Thickness	380 µm +/- 15	15 mil
Weight	440 g/m ² +/- 15	13 oz/yd ²
Finish	Matte coating	
Storage Conditions	Store boxed at 10 – 25°C (50 – 77°F)	
Shelf Life	12 months	
Processing Conditions	18 - 25°C / 64 – 77°F at 40 - 65% relative humidity	

Areas of Application

- Pop Up and Rigid display systems
- Trade show and exhibit graphics
- Recommended for indoor use

Advantages / Special Features

- High opacity film with silver light blocking back
- Matte finish to eliminate glare under fluorescent/interior lighting
- Excellent lay flat characteristics
- Scratch resistant inkjet coating
- Excellent print quality
- Fast drying
- Part of Neschen's InDisplay Solutions

Process & Handling

- To avoid fingerprints, usage of cotton gloves is recommended
- For protective purpose usage of SEAL® Protective Laminates is recommended (ensure adequate drying before lamination). 12 hours drying time is recommended.
- Store unused media in the original packaging

Recommended Protection Film

- SEAL® Print Shield Floor Guard or Print Shield Deep Crystal

* Aqueous dye based inks are prone to fading and color shift. They are recommended only for short term use.

Printability	
Waterbased, Pigment & Dye*	◆
Solvent	
UV-curable	
Latex	



March 2012

Temperatures and thicknesses are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. Neschen has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the Neschen directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards. The purchaser should test material to determine if it is suitable for their own specific purpose.