



Expression® Vacuum Presses

The preferred choice of professionals, Expression® Vacuum Presses are easy to use and are backed by a track record of consistent, outstanding performance. Guaranteed quality results every time for mounting, laminating and texturing projects.

Vacuum Press Features

- Touch-pad controls assure consistency and are user friendly
- Easy-read digital displays
- Programmable System Controller with 6 factory-installed programs for temperature and dwell time
- End-of-cycle signal
- Sturdy Dura-Box alloy frame provides a tight vacuum seal and extra durability
- Space-saving work surface
- Maintenance-free vacuum pump

The Professional's Choice for Professional Results

In the hectic pace of the framing business, Expression® Vacuum Presses are the preferred choice. The vacuum process removes moisture so time isn't lost on pre-drying work. Several pieces of varying size and thickness can be processed simultaneously to speed production. The digital microprocessor technology and touch-pad controls assure quick, efficient and easy operation.





Expression® Vacuum Press Specifications

	4468H	5298H
Working Capacity	44 x 68 x 1 in. (1117.6 x 1727.2 x 25.4 mm)	48 x 96 x 1 in. (1219.2 x 2438.4 x 25.4 mm)
Dimensions	76.25w x 56.5d x 6.5h in. (194 x 144 x 17 cm)	107.25w x 65d x 37.25h in. (273 x 165 x 95 cm)
Net Weight*	---	---
Shipping Weight	720 lb. (327 kg)	1,100 lb. (499 kg)
Power	230 VAC, 15 Amps	230 VAC, 26 Amps
Requirements	4-wire, single phase NEMA L14-20 plug (230 VAC, 15 Amps, 3-wire)**	4-wire, single phase NEMA L14-30 plug (230 VAC, 26 Amps, 3-wire)**
Pressure	13 psi	13 psi
Floor Stand	***Optional CUL Listed	Built-in CUL Listed

* Vacuum pump weight: 10.5 lb. (5kg)

** International (export) model electrical specifications

***Floor Stand Catalog numbers: 3648H-2167, 4486H-2165

All specifications subject to change without notice.

Expression Framing Products

D&K Group, Inc.

206 Cooper Street, Suite 111
Statesville, NC 28677

Customer Service: 888-240-6021

Technical Service: 888-240-6021

Tech. Fax: 704-990-2204

Hrs: 8:00 a.m.-5:00 p.m. (EST)

www.dkgroup.com

www.forframersonly.com

© 2010 D&K Group, Inc.



Equipment, heat-activated
Adhesives and Laminates
made in USA.